



12 Ch. Video Capture Card



PS-1212TI



Feature

- ⌘ Board design meets the criterion of PCI 2.2 , main chipset adopts TI642 processor.
- ⌘ Superior image quality, display at 704*576 (4CIF) , one PC can support to 32 Channels
- ⌘ H.264 Video compressed format and Audio at ADPCM.
- ⌘ Image quality and frames rate can be adjusted; Video Brightness, Hue and contrast also can be adjusted.
- ⌘ Privacy zone masking
- ⌘ Watermark supported; additionally it can work with the matched decoding device to output video to remote TV wall.
- ⌘ Support WINDOWS 2000/XP, Further development available
- ⌘ Good stability and nice resolution are your good choice for the multi-channel systems.

Specifications

Input Type	Cable12 BNC port X 1
Video Input(s)	12 channel
Audio Input(s)	12 channel, Adopt ADPCM compression standard, Collected frequency 8KHz , output rate at 32kbps
Recording Rate	360fps (NTSC), 300fps (PAL).
Compressed Format	H.264
Display Rate	360fps (NTSC), 300fps (PAL).
Display Resolution	PAL : 704*576(4CIF) NTSC : 640*480(4CIF)
Playback Resolution	PAL : 352*288(CIF) NTSC : 320*240(CIF)
Data Size	60~200M/H/C
Record	Motion detection, schedule, Alert; Privacy zone Masking for any channel. Record files can be dealt with via watermark
PTZ Control	Protocol configurable, Remote control capability, Up to 32 PTZ
Network	ISDN, DDN, PSTN, LAN, WAN, Internet, ADSL, Modem; Besides via I.E or Client software, can view multi-channels in the same, playback, manage, control and so on.

Other: It has its own player for record files to playback.